Specifications

LCD DISPLAY								
Model	**S28-A1/A2**	**ST28-A1/A2**	**S40-A1/A2**	**ST40-A1/A2**	**S50-A1/A2**	**ST50-A1/A2**	**S58-A1/A2**	**ST58-A1/A2**
Panel Type	28" TFT UHD Panel	28" TFT UHD Panel	40" TFT UHD Panel	40" TFT UHD Panel	50" TFT UHD Panel	50" TFT UHD Panel	58" TFT UHD Panel	58" TFT UHD Panel
Display size:	28"	28"	40"	40"	50"	50"	58"	58"
Active Display area	620,93 (H)x 341,28 (V)	620,93 (H)x 341,28 (V)	878,112 (H)x 485,352 (V)	878,112 (H)x 485,352 (V)	1095,84 (H)x 616,41 (V)	1095,84 (H)x 616,41 (V)	1270,08 (H)x 721,44 (V)	1270,08 (H)x 721,44 (V)
Pixel Pitch	0,16 mm (H) x 0,16 mm (v)	0,16 mm (H) x 0,16 mm (v)	0,076225 (H) x 0,2247 (v)	0,076225 (H) x 0,2247 (v)	0,0951 (H) x 0,2854 (v)	0,0951 (H) x 0,2854 (v)	0,334 (H) x 0,334 (v)	0,334 (H) x 0,334 (v)
Pixel Arrangment	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe
Backlight	Edge-LED	Edge-LED	Edge-LED	Edge-LED	Edge-LED	Edge-LED	Edge-LED	Edge-LED
backlight rated hours	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)	30000 (LED Decays to 50%)
refresh rate	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Aspect Ratio:	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Response Time:	Gray to Gray typical 1,5ms	Gray to Gray typical 1,5ms	Gray to Gray typical 8,5ms	Gray to Gray typical 8,5ms	Gray to Gray typical Avrage 9,5ms	Gray to Gray typical Avrage 9,5ms	Gray to Gray typical Avrage 9,5ms	Gray to Gray typical Avrage 9,5ms
Max. Resolution:	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160	3840 x R.G.B x 2160
HD Format	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels	Quad Full HD 3840x2160 pixels
Output frame rate	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz	QFHD 50/60 Hz
Contrast Ratio:	1000:1	1000:1	5000:1	5000:1	4000:1	4000:1	4000:1	4000:1
Brightness (cd/m2):	300 cd/m^2	300 cd/m^2	350 cd/m^2	350 cd/m^2	350 cd/m^2	350 cd/m^2	350 cd/m^2	350 cd/m^2
Display Color (Max):	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)	1,07G corlars (8-bit +FRC)
Viewing Angle:	H:170° V:160° VA Technology	H:170° V:160° VA Technology	H:176° V:176° VA Technology	H:176° V:176° VA Technology	H:176° V:176° VA Technology	H:176° V:176° VA Technology	H:176° V:176° VA Technology	H:176° V:176° VA Technology
Ultra wide viewing technology	a-si-TFT Active matrix	a-si-TFT Active matrix	Super VMA Technology	Super VMA Technology	Super VMA Technology	Super VMA Technology	Super VMA Technology	Super VMA Technology
Display operation mode	Transmissive mode/Normaly White	Transmissive mode/Normaly White	Transmissive mode/Normaly black	Transmissive mode/Normaly black	Transmissive mode/Normaly black	Transmissive mode/Normaly black	Transmissive mode/Normaly black	Transmissive mode/Normaly black
Surface treatment	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H	Anti-Glare coating (Haze 1%) Hardness 3H
Accessories included	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw	Base,Remote,AC-Cable, Screw
Remote Type	2,4 GHz	2,4 GHz	2,4 GHz	2,4 GHz	2,4 GHz	2,4 GHz	2,4 GHz	2,4 GHz
Remote Pairing	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)	Reciver key + 2 remote keys (ok+0)
Display								
High color saturation	NTSC 72%	NTSC 72%	NTSC 88%	NTSC 88%	NTSC 88%	NTSC 88%	NTSC 88%	NTSC 88%
Sound System:	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT	Stereo /Surround/ SRS TruSurround XT
AUDIO								
Stereo system:	Stereo	Stereo	Stereo	Stereo	Stereo	Stereo	Stereo	Stereo
Audio Speaker:	10W X 2	10W X 2	10W X 2	10W X 2	10W X 2	10W X 2	10W X 2	10W X 2
CONNECTION								
CVBS +Audio R/L Input:	X 1	X 1	X 1	X 1	X 1	X 1	X 1	X 1
Analog VGA:	X 1	X 1	X 1	X 1	X 1	X 1	X 1	X 1
PC Stereo Input:	X 1	X 1	X 1	X 1	X 1	X 1	X 1	X 1
HDMI 1 ARC /CEC	X1	X1	X1	X1	X1	X1	X1	X1
HDMI 2	X1	X1	X1	X1	X1	X1	X1	X1
HDMI 3 MHL	X1	X1	X1	X1	X1	X1	X1	X1
YCbCr/YPbPr Input:	X1	X1	X1	X1	X1	X1	X1	X1
Coaxial Out:	X1	X1	X1	X1	X1	X1	X1	X1
USB Media Player 1	X1	X1	X1	X1	X1	X1	X1	X1
USB Media Player 2	X1	X1	X1	X1	X1	X1	X1	X1
On/OFF key	X1	X1	X1	X1	X1	X1	X1	X1
Remote Pair Key	X1	X1	X1	X1	X1	X1	X1	X1
Touch Screen USB	No	X1	No	X1	No	X1	No	X1
USB Connection	-	Yes	-	Yes	-	Yes	-	Yes
Touch screen 6point	-	-	-	Yes	-	Yes	-	Yes
Touch screen 10 point	-	10 point	-	Optional	-	Optional	-	Optional
Touch Type	-	IR (Infra red) touch	-	IR (Infra red) touch	-	IR (Infra red) touch	-	IR (Infra red) touch
Touch interface	-	USB 2.0	-	USB 2.0	-	USB 2.0	-	USB 2.0
Touch OS Support	-	Windows/Linux/Android/Mac	-	Windows/Linux/Android	-	Windows/Linux/Android	-	Windows/Linux/Android
Sensing Object	-	Pen/Finger	-	Pen/Finger	-	Pen/Finger	-	Pen/Finger
Touch resolution	-	4096 x 4096	-	4096 x 4096	-	4096 x 4096	-	4096 x 4096
Protective glas	-	Yes	-	Yes	-	Yes	-	Yes
Signal Mode								
CVBS +Audio R/L Input:	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms	Pal/Secam/NTSC 1Vp-p@75ohm 500mVrms
Analog VGA:	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz	H:30-75KHz V:56-75Hz 0,7Vp-p@75ohm Max 1920x1080@60Hz
PC Stereo Input:	500mVrms	500mVrms	500mVrms	500mVrms	500mVrms	500mVrms	500mVrms	500mVrms
HDMI:	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible	HDMI2,0/1,4b /HDCP 2,2/1,4 MHL 3,0/2,1 Compatible
YCbCr/YPbPr Input:	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P	Y:1Vp-p@75ohm, PbPr: 0,7Vp-p@75ohm 500mVrms 480I/P, 576I/P, 720P,1080I/P
USB Media Player 1	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
USB Media Player 2	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
POWER								
Valtage/Frequency:	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz	AC Input 100~240V,50/60Hz
Power Consumpiton:	Max 45 Watt	Max 45 Watt	Max 65 Watt	Max 65 Watt	Max 135 Watt	Max 135 Watt	Max 165 Watt	Max 165 Watt
Stand by Power consumption:	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W
FEATURES								
Full HD Compitable	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P	480i/576i,480p/576p,720p/1080i /1080P 2160i/2160P
HDMI Input	3 HDMI	3 HDMI	3 HDMI	3 HDMI	3 HDMI	3 HDMI	3 HDMI	3 HDMI
HDMI 4k @50Hz / 60Hz	Yes in All inputs	Yes in All inputs	Yes in All inputs	Yes in All inputs	Yes in All inputs	Yes in All inputs	Yes in All inputs	Yes in All inputs
HDMI Auto EDID Swith 1.4b / 2.0	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
3D Digital Comb Filter	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
3D Digital Noise Reduction	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Sleep timer	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Advanced Timer	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power on/off timer	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Smart HDMI	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
HDMI 1 ARC	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
HDMI 3 MHL	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible	MHL 3,0/2,1 Compatible
HDMI 1 CEC	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Color temperature control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Picture Status Memory	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi display mode	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
USB Media player	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB play list	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Auto play mode Video	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Auto play mode Photo	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Auto play mode Video/Photo	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Simple mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB Play list mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
De-Interlace	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video	3D motion adaptive video
Cooling FAN (2 UNIT)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cooling FAN ON/OFF	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cooling FAN ON Tempureture control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cooling FAN Speed mode High/Medium/Low	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
High temperture turn OFF protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
High temperture turn OFF protection messsage	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Brightness adjust option	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Protection back door	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lockable back door	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PC / Android mounting space inside	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
External Power Switch ON/OFF	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Extra power extention inside	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
External acssesable USB port	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
External acssesable LAN port	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Friendly 2,4 GHz Remote Access	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote 2,4 GHz access Max distance	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m
Easy Multiple machine remote access	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote 2,4 GHz have different connection ID	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote 2,,4 GHz Can controll just paired display	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Vertical / Horizental OSD Rotate	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Ye

Specifications

LCD DISPLAY								
Model	**S28-A1/A2**	**ST28-A1/A2**	**S40-A1/A2**	**ST40-A1/A2**	**S50-A1/A2**	**ST50-A1/A2**	**S58-A1/A2**	**ST58-A1/A2**
Aspec ratio	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2	Point to Point/ Just scan/ Auto/ 16:9/ 4:3/ Panorama/ Zoom1/ Zoom2
Local Dimming ON/OFF	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OSD Language	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese	English, Swedish, Japan, German, Italy ,France, Chinese
Dimension								
dimension with base	w 813x h 1820x d 450 mm	w 813x h 1820x d 450 mm	w 676x h 1817x d 440 mm	w 676x h 1817x d 440 mm	w 813x h 1820x d 450 mm	w 813x h 1820x d 450 mm	w 916x h 1820x d 450 mm	w 916x h 1820x d 450 mm
dimension w/t base	w 747x h 1802x d 66 mm	w 747x h 1802x d 66 mm	w 610x h 1799x d 66 mm	w 610x h 1799x d 66 mm	w 747x h 1802x d 66 mm	w 747x h 1802x d 66 mm	w 850x h 1802x d 66 mm	w 850x h 1802x d 66 mm
Thikness upper part	41,50 mm	57 mm	41,50 mm	41,50 mm	41,50 mm	57 mm	41,50 mm	57 mm
Packing Size	L 1940 x W 900 x H 160 mm	L 1940 x W 900 x H 160 mm	L 1940 x W 770 x H 160 mm	L 1940 x W 770 x H 160 mm	L 1940 x W 900 x H 160 mm	L 1940 x W 900 x H 160 mm	L 1940 x W 1000 x H 160 mm	L 1940 x W 1000 x H 160 mm
Gross wieght	47KG	52KG	47KG	53KG	57KG	64KG	65KG	75KG
Net wieght	39KG	44KG	35KG	41KG	43KG	51KG	50KG	60KG
Quantity/Pallet	5	5	5	5	5	5	5	5
Pallet Size	800 W x 1940 L x1050 H	800 W x 1940 L x1050 H	800 W x 1940 L x920 H	800 W x 1940 L x920 H	800 W x 1940 L x1050 H	800 W x 1940 L x1050 H	800 W x 1940 L x1150 H	800 W x 1940 L x1150 H
Other packing	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)	Flight Case avalible (Optional)
Operating Condition								
Temperature	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C	Normal Condtion 20± 15°C
Humidity	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%	Normal Condtion 55± 20%
Operating Ambient Temp.	0°C - 50°C	0°C - 50°C	0°C - 50°C	0°C - 50°C	0°C - 50°C	0°C - 50°C	0°C - 50°C	0°C - 50°C
Storage Temp.	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C	Min -20°C / Max +60°C
Color								
Front Standard	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1	Glossy Black Code A2/ Glossy white Code A1
Front Finnishing	High Glossy	High Glossy	High Glossy	High Glossy	High Glossy	High Glossy	High Glossy	High Glossy
Back Standard	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1	Black Code A2/ White Code A1
Back Finnishing	Powder coated	Powder coated	Powder coated	Powder coated	Powder coated	Powder coated	Powder coated	Powder coated
Edge Standard	Chrome	Chrome	Chrome	Chrome	Chrome	Chrome	Chrome	Chrome
Edge Finnishing	Brushed aluminium	Brushed aluminium	Brushed aluminium	Brushed aluminium	Brushed aluminium	Brushed aluminium	Brushed aluminium	Brushed aluminium
Other colors	Open request	Open request	Open request	Open request	Open request	Open request	Open request	Open request
Accessories								
Base Enhancer	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)	YES (5mm metal plate)
Mobile Base Enhancer (1,5inch wheel)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)	YES (5mm metal plate with 6 unit 1,5 inch lockable wheels)
Mobile Base Enhancer (3inch wheel)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)	YES (5mm metal plate with 6 unit 3 inch lockable wheels)
Extra Fixing enahcer unit	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)	Yes (3mm metal plate at the base edge+10 Screws)
Side Shelf right or left	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)
Side Shelf color	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)
Front/Back Shelf	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)	YES (Black code A2/ White Code A1)
Top edge Logo Holder	YES	YES	YES	YES	YES	YES	YES	YES
Top edge plexi logo (custom)	YES	YES	YES	YES	YES	YES	YES	YES
Protection ring	YES	YES	YES	YES	YES	YES	YES	YES
Custom LED lighted logo Front	YES	YES	YES	YES	YES	YES	YES	YES
External WIFI Antenna	YES	YES	YES	YES	YES	YES	YES	YES
Packing Quantity								
20" FCL	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs
40" FCL	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs
40" HQ	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs	**pcs